



MØRE TRAFØ AS
HOVEDKONTOR
N-6230 SYKKYLVEN
TLF.: 47 -70 24 61 00
FAX : 47 -70 24 61 01

22000

+ -- 2 x 2,5 %

3 -fase

Kobl.

50 Hz

Kjøling

/ 240

Volt

Yyn0

ONAN

Overflate

EP 96056

E =EPOXY

Fargekode

NCS 6010 G 60 Y

Tiln. RAL6013

V=Vfz (zink)

Kjerneblikk

Step-lap

Laser

Godkjent olje :

Type :

NYTRO 10XN

Mineralolje

zt > 7,3%

more.trafo@moretrafo.no

Hermetisk tett

Skal ikke åpnes ved vedlikehold !

IEC60076-1-2000

315>>>

		Ny !	Ny !	Ny !	Ny !	Ny !	Ny !	Ny !	Ny !	Ny !	Ny !	Ny !	Ny !
Type :		OTK	OTW	OTW	OTW	OTW	OTW	OTW	OTK	OTW	OTW	OTK	OTW
2528		3625	3640	4640	4650	51160	6570	6960	6970	8570	81078	81078	
30		50	100	200	315	500	630	800	1 000	1 250	1 600	1 600	
22000 Volt		AI	AI	AI	AI	AI	AI	AI	AI	AI	AI	AI	AI
Viklinger HS													
Viklinger LS													
Kurs	8,50												
Tomg.tap Po:	1,02	W	60	120	150	210	380	470	590	650	900	960	1100
Tomg.strøm lo:		%		2,18	0,50	0,47	0,35	0,24	0,13	0,13	0,18	0,16	0,12
Bel.tap Pk:		W	13,8	920	860	1470	2070	3340	4360	7280	6750	9170	12270
(ek ,uk ,uz,Ucc ,Vcc) :		zt % :		4,13	3,66	3,81	3,74	4,37	4,33	4,72	5,58	6,23	6,06
		rt % :		3,05	1,71	1,47	1,03	1,06	0,87	1,16	0,84	0,92	0,98
		xt % :		2,79	3,24	3,52	3,59	4,24	4,24	4,58	5,52	6,17	5,98
Reaktive tg. Qo:		kVAr		0,65	0,21	0,42	0,60	0,61	0,30	0,48	1,19	1,25	1,07
Reaktive bel.Qk:		kVAr		0,84	1,62	3,52	7,18	13,35	21,18	28,85	44,14	61,65	74,76
Komp.full last		kVAr		1,48	1,83	3,93	7,78	13,96	21,49	29,33	45,33	62,90	75,83
		Ro mOhm		58,56	19,699	8,461	2,976	1,939	1,004	1,057	0,607	0,528	0,452
		Xo mOhm		651,686	270,213	227,059	100,08	90,322	67,554	81,132	50,44	50,44	39,198
Spenn.fall dU %													
Belastn.faktor	1,0	cosØ:	1,0	3,09	1,71	1,47	1,03	1,15	0,96	1,26	1	1,11	1,16
Belastn.faktor	1,0	cosØ:	0,8	4,11	3,31	3,28	2,98	3,43	3,28	3,72	4,06	4,53	4,46
Virkn.grad % :													
Belastn.faktor	1,0	cosØ:	1,0	96,68	98,04	98,35	98,79	98,81	99,02	98,76	99,06	99,00	98,94
Belastn.faktor	1,0	cosØ:	0,8	95,87	97,57	97,94	98,50	98,51	98,78	98,45	98,82	98,75	98,68
Belastn.faktor	0,75	cosØ:	0,8	96,60	97,97	98,30	98,74	98,78	99,00	98,76	99,04	98,99	98,95
Belastn.faktor	0,5	cosØ:	1,0	97,73	98,60	98,86	99,12	99,18	99,34	99,22	99,36	99,36	99,34
Design omg.	20	°C											
Belastn.faktor	1,0	cosØ:	1,0										
Oljetrykk dP		bar		0,20	0,20	0,18	0,14	0,26	0,22	0,10	0,20	0,16	0,06
Lydeff. LwA		dB		37	37	39	44	49	51	53	54	56	57
Lydtr. LpA		dBA		27	27	28	35	40	42	43	45	45	46
Lydint. LIA		dBA											
Flukstetthet kjerne		Tesla		1,79	1,53	1,66	1,64	1,72	1,58	1,63	1,69	1,69	1,59
Ref. sec. max Ik		kA		1,7	3,3	6,3	12,9	17,3	27,8	32,1	34,5	38,6	49,6
Overflate	E=Epoxy, V=Vfz			V	V	V	V	E	E	E	E	E	E
GJENVINNING	Vekt %			92,7	94,8	94,5	96,2	96,6	97,5	97,5	97,7	97,7	97,9
Dim.:	Ref. dim.			V26556	V50476	V49478	V50307	V50308	V46206	V25900	V43291	V44345	V28148
	kVA			30	50	100	200	315	500	630	800	1000	1250
Total	kg			336	511	572	888	1 099	1 774	1 966	2 292	2 551	3 317
Olje	kg			132	172	155	188	238	335	402	448	493	670
Kjerne & vikl.	kg			145	263	341	591	702	1 155	1 171	1 503	1 666	2 064
Olje	0,876 Liter			151	196	177	215	272	382	459	511	563	765
Total Lengde L =	mm			810	940	940	1 120	1 110	1 280	1 460	1 500	1 600	1 730
Total Bredde B =	mm			580	670	670	730	790	830	880	900	900	1 050
Total Høgd H =	mm			1 070	1 070	1 070	1 090	1 400	1 570	1 690	1 590	1 690	1 900
Måiskisse				T88402c	T109469c	T109469c	T111433a	T111434c	T105456a	T88405a	T101441b	T102496b	T93402c
Gjennomf. HS				Porselen	Porselen	Porselen	Porselen	Porselen	Porselen	Porselen	Porselen	Porselen	Porselen
Gjennomf. LS	Mxx	mm		12	12	12	20	30	30	42	42	48	48
Gjennomf. LS	Mxx	mm	n	12	12	12	20	12	12	12	12	12	20

T92458

	H2	mm	700	700	700	720	870	1 040	1 160	1 060	1 160	1 320	1 590	1 590
a1	mm		670	670	670	670	670	670	670	670	670	820	820	820
c1	mm		380	450	450	510	510	540	540	540	540	600	690	690
c2	mm		420	490	490	550	550	600	600	600	600	650	860	860
a	mm		698	828	828	978	978	1 150	1 210	1 350	1 350	1 500	1 660	1 660
c	mm		358	428	428	488	488	520	470	570	570	580	686	686
f1	mm		135	157	157	190	190	188	167	205	205	205	248	248
f2	mm		130	115	115	140	140	144	128	178	178	170	175	175
g	mm		80	250	250	300	150	175	180	210	210	235	260	260
i	mm		60	250	250	300	75	92	90	105	105	118	130	130
k	mm		300	305	305	275	275	300	300	300	300	300	300	300
m	mm		300	305	305	138	138	300	300	300	300	300	300	300
p	mm		450	665	665	820	820	915	960	1 140	1 140	1 200	1 420	1 420

08.03.2010

Σ